

## **4155110**

SZ Universal light with socket



# Technical

<b>Description</b>	Compact fluorescent tube 18 W with high luminosity.
<b>Benefits</b>	Simple, fast assembly
<b>Installation options</b>	TS horizontal section of the roof frame: direct TS, SE vertical section: with TS adaptor bracket SE sections at the front and rear of the roof frame: with TS adaptor bracket SE extrusions at the side of the roof frame: direct AE, CM, TP: with universal bracket AE: with rail for interior installation
<b>Material</b>	Plastic
<b>Supply includes</b>	Universal light Integral motion detector Light Light cover Assembly parts
<b>Dimensions</b>	Width: 345 mm Height: 95 mm Depth: 55 mm
<b>Rated operating voltage</b>	110 V - 240 V, 1~, 50 Hz/60 Hz
<b>Equipment (electrical)</b>	Ballast: Wide-range electronic ballast Light: Compact fluorescent lamp, base 2G11 Jack/socket (type): D, earthing-pin (type F, CEE 7/3) Integral motion detector: yes Switch (type): Integral, on/off/motion detector mode
<b>Operating temperature</b>	Operation (environment): -15°C...+45°C Bearing: -20°C...+70°C
<b>Power consumption</b>	18 W
<b>Rated insulation voltage</b>	250 V AC
<b>Rated impulse withstand voltage, phase to phase</b>	2500 V AC
<b>Protection category</b>	I (PE conductor)
<b>Light - installation type</b>	Screw-fastening
<b>Connection options</b>	Power supply via connectors Through-wiring (creating rows of lights)
<b>Light cover</b>	yes

---

<b>Packs of</b>	1 pc(s).
<b>Weight/pack</b>	0.92 kg
<b>EAN</b>	4028177679832
<b>Customs tariff number</b>	94054095
<b>ETIM 6.0</b>	EC000321
<b>ETIM 5.0</b>	EC000321
<b>eCI@ss 8.0/8.1</b>	27189241
<b>eCI@ss 7.0/7.1</b>	27189241
<b>eCI@ss 6.0/6.1</b>	27189241
<b>eCI@ss 5.1/5.1.4</b>	27189241

---

Datasheet generated from <https://onetimepim.com> last updated Thursday, January 23, 2020 11:01:03 AM