



5509131

TS IT RAL7035 WHD 800x2000x1000 42U



Technical

Note	Depending on the siting type and location, the door opening may vary for selected applications For enclosures with height and depth 2000 x 1200 mm / 2200 x 1000 mm / 2200 x 1200 mm, the matching side panels are optionally available and are supplied fitted to the enclosure
Material	Sheet steel Aluminium Glazed aluminium door with 3 mm single-pane safety glass
Surface finish	Enclosure frame: Dipcoat-primed Interior installation: Dipcoat-primed Doors and roof: Dipcoat-primed, powder-coated
Colour	Enclosure frame and panels: RAL 7035 Interior installation: RAL 9005
Protection category IP to IEC 60 529	IP 55 only in conjunction with baying seal or screw-fastened side panels
Supply includes	TS 8 enclosure frame with doors and roof plate Glazed aluminium door at the front, 180° hinges Sheet steel door at the rear, 180° hinges Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E Roof plate, one-piece, solid Base tray and gland plate, multi-piece, solid Two 482.6 mm (19") mounting frames, front and rear, depth-variable Baying seal and sealing kit for gland plates (supplied loose) Connection accessories for potential equalisation with earthing point (supplied loose) 50 multi-tooth screws M5, cage nuts M5, conductive (supplied loose) IPPC pallet
Basic material	Sheet steel
Dimensions	Width: 800 mm Height: 2000 mm Depth: 1000 mm
Installation height for components	42 U
Distance between levels as delivered	745 mm
Load capacity	482.6 mm (19") level: 10000 N
Packs of	1 pc(s).
Weight/pack	134.8 kg
EAN	4028177705777
Customs tariff number	94032080

ETIM 6.0	EC002499
ETIM 5.0	EC002499
eCI@ss 8.0/8.1	27180207
eCI@ss 7.0/7.1	27180207
eCI@ss 6.0/6.1	27180207
eCI@ss 5.1/5.1.4	27180201

Datasheet generated from <https://onetimepim.com> last updated Thursday, January 23, 2020 11:01:06 AM