

7507200

DK FLATBOX 15HE, WxD 700x700 mm



Technical

Description	For flexible use as a wall-mounted or floor-standing enclosure.
Note	Max. installation depth: Depth - 58 mm to rear panel Max. distance between two 482.6 mm (19") levels: Depth - 104 mm
Benefits	Tool-free quick assembly System assembly on the open 482.6 mm (19") frame
Material	Sheet steel Viewing window: Single-pane safety glass, 3 mm
Surface finish	Powder-coated
Colour	RAL 7035
Supply includes	Flat-packed enclosure 1 wall section 2 basic supports 2 roof/base plates, with cut-outs for cable entry via brush strips 2 side panels, lockable 1 glazed door, lockable, security lock 3524 E, door hinge point selectable Connection components for tool-free, fast assembly Earthing kit for system-compatible earthing of all enclosure parts 1 482.6 mm (19") mounting frame 4 Levelling feet
Design	with 482.6 mm (19") mounting frame
Basic material	Sheet steel
Dimensions	Width: 700 mm Height: 758 mm Depth: 700 mm
Installation height for components	15 U
Packs of	1 pc(s).
Weight/pack	42 kg
EAN	4028177551466
Customs tariff number	94032080
ETIM 6.0	EC002500
ETIM 5.0	EC002500
eCI@ss 8.0/8.1	27180208

eCI@ss 7.0/7.1	27180208
eCI@ss 6.0/6.1	27180208
eCI@ss 5.1/5.1.4	27180204

Datasheet generated from <https://onetimepim.com> last updated Thursday, January 23, 2020 11:01:12 AM