

Techlogiks Canada Inc.

Category 6 Unshielded Keystone Jack

Techlogiks Cat 6 Unshielded Keystone Jack is designed to easily snap in and out of the wall outlet, patch panel and surface mount box. It is individually terminated using Insulation Displacement Connectors (IDC) with punch down tool for quick installation.





Applications

- 1000BASE-T, 100BASE-Tx, 10BASE-T, 155M ATM, 4/16MB Token Ring.
- 100Mbps TP-PMD, ISDN, ADSL, Analog & Digital Voice (VoIP) / Video.
- Power over Ethernet (PoE), Control Signal.





Standards

- Lead-free & RoHS2 compliant.
- ANSI/TIA-568-C.2, ANSI/TIA-1096-A (FCC Part 68), ISO/IEC 11801 2nd edition and CENELEC EN 50173-1.
- Level A reliability requirements of IEC 60603-7-2 and IEC 60603-7-4 for RJ45.
- Compatible for T568A and T568B wiring schemes.

| Specifications | | |
|----------------------|--|--|
| Сар | High impact Acrylonitrile Butadiene Styrene (ABS resin), UL 94 V-0 rated | |
| Housing | High impact Acrylonitrile Butadiene Styrene (ABS resin), UL 94 V-0 rated | |
| Jack Contacts | Phosphor bronze flat wire plated with hard gold over nickel under plate on contact area, plated with tin over nickel under plate on solder area. | |
| PCB | FR4 | |
| IDC Block | High impact Polycarbonate (PC resin), UL 94 V-0 rated, RoHS compliant. | |
| Conductor Diameters | 24 AWG – 22 AWG | |
| Insulation Diameters | 0.8mm – 1.0mm | |
| Cable Diameters | 5mm – 9mm | |

| Electrical Characteristics | | | |
|-----------------------------|--|--|--|
| Voltage proof: | 1000V DC or AC peak, contact-to-contact. | | |
| Current-carrying capacity: | 0.75Amps minimum | | |
| Contact resistance: | 20mohm maximum | | |
| Insulation resistance: | 500Mohm minimum at 100V DC | | |
| Input to output resistance: | 200mohm maximum | | |
| DC resistance: | 0.2ohm maximum | | |

| Mechanical Characteristics | | |
|---|--|--|
| Mechanical operation | 750 cycles min. for insertion / withdrawal with modular plug. 20 cycles min. for cable re-termination. | |
| Effectiveness of connector coupling devices | 50N (11lbf) for 60s ± 5s. | |

| Environmental Characteristics | | | |
|-------------------------------|--------------|--|--|
| Temperature | -10°C ~ 60°C | | |
| Humidity | 10% ~ 90%RH | | |

| ORDERING INFORMATION | |
|----------------------|---|
| PART NUMBER | DESCRIPTION |
| TL-JHC6U | Cat 6 Unshielded Keystone Jack, (White/ Red/ Ivory/ Black) |